

# HS-5T

## Automatic Gyroscopic Mixer

Patent NO. ZL 2007 2 0052569.8  
Patent NO. ZL 2007 2 0052568.3

This gyroscopic mixer is the perfect solution for fast and homogeneous mixing of paint and similar materials. This unit automatically clamps the product can adjusting the clamping force and the mixing speed to the inserted can size. Operator's safety is granted by the most strict design and material specifications.



HS-5T

H.PU® 弘普

### Basic features

- Fully automatic gyroscopic mixer
- Unique alternate mixing direction
- Automatic can clamping mechanism
- Can proportional mixing speed (100 - 150 RPM) and clamping force
- Adjustable mixing time from 1 to 10 minutes
- The lower can tray can be extracted for easy can loading and unloading
- High contrast LCD display
- Safety switch on the access door

### Options

- 110 V 60 Hz power settings
- Custom body colors

### Can handling


- Maximum load 35 Kg (77 lb.)
- Maximum can height 420 mm
- Minimum can height 60 mm
- Maximum can diameter 330 mm

### Power and electric specs.

- Single phase 220 V 50 Hz  $\pm$  10%
- Max. power consumption 750 W
- Working temperature from 10° to 40°
- Relative humidity from 5% to 85% (not condensing)

### Dimensions and shipping

- Size (H, W, D) 1040 x 800 x 770 mm
- Weight 175 Kg (386 lb.)
- Wood crate standard packaging
- Shipping size (H, W, D) 1180 x 900 x 810 mm
- Shipping weight 212 Kg (467 lb.)
- 20' Container can contain up to 28 units (56 units in 40')



control panel



### HONGPU MACHINERY MANUFACTURE CO., LTD.

Add: North Industrial Rd., Lunjiao, Shunde, Guangdong, China  
postcode: 528308  
TEL: +86 757 2362 3133 / 2362 3138  
FAX: +86 757 23622787  
E-mail: info@hpuchina.com  
http://www.hpuglobal.com

Above pictures and specification for reference only, subject to change without prior notice.